

-2-

IN THE CLAIMS:

Please cancel claims 21-40 without prejudice.

1. (Previously Presented) A method for discovering resources in a network of user nodes, said method comprising the steps of:

receiving a resource request to be published at a first user node of the network;

determining whether or not to send the resource request to a publish-subscribe server

node;

forwarding the resource request to a second user node of the network, when it is determined not to send the resource request to the publish-subscribe server node; and

sending the resource request to the publish-subscribe server node for publication to a plurality of the user nodes of the network, when it is determined to send the resource request to the publish-subscribe server node.

2. (Previously Presented) The method as defined in claim 1, wherein in the determining step, the determination of whether or not to send the resource request to the publish-subscribe server node is a random decision made by the first user node.

3. (Previously Presented) The method as defined in claim 2, wherein in the determining step, the random decision is made based on a weighting factor corresponding to the probability that the first user node will decide to send the resource request to the publish-subscribe server node.

4. (Original) The method as defined in claim 1, wherein the forwarding step includes the sub-steps of:

randomly selecting one of the user nodes to which the first user node is connected to be the second user node; and

forwarding the resource request from the first user node to the second user node through a direct connection.

-3-

5. (Previously Presented) The method as defined in claim 1, further comprising the step of sending, via publication from the publish-subscribe server node, the resource request to at least some of the user nodes of the network.

6. (Previously Presented) The method as defined in claim 5, wherein in the step of sending via publication from the publish-subscribe server node, the publish-subscribe server node sends the resource request to all of the user nodes of the network that are subscribed to one or more selected resource request channels.

7. (Previously Presented) The method as defined in claim 1, further comprising the step of repeating the steps of determining and forwarding until in the determining step a user node that received the resource request decides to send the resource request to the publish-subscribe server node.

8. (Original) The method as defined in claim 1, further comprising the steps of:  
    sending the resource request to be published from a requesting user node, which desires the request resource, to the first user node; and  
    sending an identical resource request from the requesting user node to all of the user nodes to which the requesting user node is connected through direct connections.

-4-

9. (Previously Presented) A machine-readable medium encoded with a program for discovering resources in a network of user nodes, said program containing instructions for performing the steps of:

- receiving a resource request to be published at a first user node of the network;
- determining whether or not to send the resource request to a publish-subscribe server

node;

- forwarding the resource request to a second user node of the network, when it is determined not to send the resource request to the publish-subscribe server node; and

- sending the resource request to the publish-subscribe server node for publication to a plurality of the user nodes of the network, when it is determined to send the resource request to the publish-subscribe server node.

10. (Previously Presented) The machine-readable medium as defined in claim 9, wherein in the determining step, the determination of whether or not to send the resource request to the publish-subscribe server node is a random decision made by the first user node.

11. (Previously Presented) The machine-readable medium as defined in claim 10, wherein in the determining step, the random decision is made based on a weighting factor corresponding to the probability that the first user node will decide to send the resource request to the publish-subscribe server node.

12. (Original) The machine-readable medium as defined in claim 9, wherein the forwarding step includes the sub-steps of:

- randomly selecting one of the user nodes to which the first user node is connected to be the second user node; and

- forwarding the resource request from the first user node to the second user node through a direct connection.

-5-

13. (Previously Presented) The machine-readable medium as defined in claim 9, wherein said program further contains instructions for performing the step of sending, via publication from the publish-subscribe server node, the resource request to at least some of the user nodes of the network.

14. (Previously Presented) The machine-readable medium as defined in claim 13, wherein in the step of sending via publication from the publish-subscribe server node, the publish-subscribe server node sends the resource request to all of the user nodes of the network that are subscribed to one or more selected resource request channels.

15. (Previously Presented) The machine-readable medium as defined in claim 9, wherein said program further contains instructions for performing the step of repeating the steps of determining and forwarding until in the determining step a user node that received the resource request decides to send the resource request to the publish-subscribe server node.

16. (Original) The machine-readable medium as defined in claim 9, wherein said program further contains instructions for performing the steps of:

    sending the resource request to be published from a requesting user node, which desires the request resource, to the first user node; and

    sending an identical resource request from the requesting user node to all of the user nodes to which the requesting user node is connected through direct connections.

-6-

17. (Currently Amended) A user node for use in a computer network of the type that includes a plurality of user nodes and at least one publish-subscribe server node, with each of the user nodes being connected to at least one other user node through a direct connection, said user node comprising:

a receiving interface for receiving a resource request to be published;

control means for deciding whether or not to send the resource request to the publish-subscribe server node; and

at least one transmitting interface for selectively forwarding the resource request to a second user node of the network or sending the resource request to the publish-subscribe server node for publication,

wherein the transmitting interface forwards the resource request to the second user node when the control means decides not to send the resource request to the publish-subscribe server node, and sends the resource request to the publish-subscribe server node for publication to a plurality of the user nodes of the network when the control means decides to send the resource request to the publish-subscribe server node.

18. (Previously Presented) The user node as defined in claim 17, wherein the control means randomly decides whether or not to send the resource request to the publish-subscribe server node.

19. (Original) The user node as defined in claim 18, wherein the control means randomly decides based on a weighting factor.

20. (Original) The user node as defined in claim 17, wherein the control means randomly selects one of the other user nodes of the network to be the second user node to which the resource request is forwarded.

Claims 21-40. (Canceled)